



The 2 Gbit/sec Brocade SilkWorm 3900 Enterprise Fabric Switch provides an entry point to enterprise SANs, improving availability, performance, and manageability at an attractive price.

## SILKWORM 3900

### Highlights

- Provides 32 ports in a 1.5U enclosure along with auto-sensing 1 and 2 Gbit/sec interfaces for seamless integration with existing fabrics
- Leverages Brocade Advanced Fabric Services to provide the highest levels of SAN performance, security, and manageability
- Meets mission-critical availability requirements with network resiliency, automatic data path rerouting, non-disruptive software upgrades, and redundant, hot-pluggable components
- Increases performance by employing Brocade Inter-Switch Link (ISL) Trunking to create a data path with up to 8 Gbit/sec throughput per trunk
- Provides substantial cost savings by supporting a SAN infrastructure that increases productivity, maximizes IT resource utilization, and reduces capital expenditures

## Increased Flexibility for Evolving SAN Requirements


The Brocade® SilkWorm® 3900 32-port, auto-sensing Fibre Channel switch provides an intelligent and cost-effective solution to meet a wide range of Storage Area Network (SAN) requirements. As the latest addition to the Brocade 2 Gbit/sec fabric switch family, the SilkWorm 3900 is ideal for organizations that face rapidly changing storage requirements.

With the performance capabilities of an enterprise switch and the cost-effectiveness of a modular switch solution, the SilkWorm 3900 enables a flexible SAN infrastructure. Designed for midsize to large storage networks, the SilkWorm 3900 enables organizations to implement a SAN infrastructure that best meets

their current needs and expands seamlessly as their storage requirements evolve. The SilkWorm 3900 provides a complete solution for a departmental SAN fabric, as a small core, or an edge switch extending the reach of an enterprise core-to-edge SAN built around the Brocade SilkWorm 12000 Core Fabric Switch (see Figure 1).

Based on a third-generation Brocade intelligent architecture, the SilkWorm 3900 provides a highly available, scalable, and secure foundation for SAN applications such as high-speed data backup, server and storage consolidation, remote mirroring, and long-distance data replication.

**Figure 1.** The SilkWorm 3900 provides a reliable building block for departmental SANs and a high-performance edge switch for enterprise core-to-edge SANs.



#### HIGH AVAILABILITY FOR BUSINESS CONTINUANCE

By combining the proven reliability of the SilkWorm switch family with a wide range of hardware and software availability features—such as seamless upgrades of switch software—the SilkWorm 3900 supports a SAN fabric capable of delivering overall system availability greater than 99.999 percent.

The core-to-edge SAN model uses redundant fabrics, hot-pluggable components, and multiple data paths to help ensure high availability across the fabric. In addition, Brocade Fabric Shortest Path First (FSPF) enables the fabric to automatically isolate problems and reroute traffic around failed links onto alternate paths. As a result, the SilkWorm 3900 provides a SAN infrastructure solution that is designed to meet the most demanding business continuance requirements.

#### INDUSTRY-LEADING PERFORMANCE

The SilkWorm 3900 provides numerous business advantages for organizations that want to increase application performance and operational productivity. It can deliver up to 128 Gbit/sec of aggregated throughput, with 32 ports capable of 2 Gbit/sec full-duplex performance. To achieve even higher performance, organizations can use


Brocade ISL Trunking, which combines as many as four ISLs into a single logical ISL with up to 8 Gbit/sec throughput.

Fibre Channel speed is also possible at longer distances for remote operations. By leveraging the Brocade Extended Fabrics feature and Dense Wave Division Multiplexing (DWDM) technology, storage networks can span up to 100 km over Metropolitan Area Networks (MANs) at high speed—significantly enhancing disaster recovery operations.

#### A DESIGN TO LEVERAGE INTELLIGENCE IN THE FABRIC

To help maximize IT investments and reduce costs, the SilkWorm 3900 is designed to leverage the industry's only intelligent fabric services architecture. The proven intelligence in the Brocade Fabric OS and third-generation Brocade ASIC technology enables the high levels of security, management, and performance required by the most demanding SAN environments.

Organizations can utilize leading capabilities such as frame filtering and Brocade Advanced Fabric Services to unlock the intelligence of the Brocade SAN fabric for a variety of applications. For instance, Brocade Advanced Zoning enables organizations to implement robust,



hardware-enforced zoning based on World Wide Name (WWN). Advanced Performance Monitoring provides fabric-wide performance analysis to support tasks such as load balancing and application charge-back. And ISL Trunking provides 8 Gbit/sec throughput to support high-performance applications.

#### OPEN SAN MANAGEMENT

The SilkWorm 3900 simplifies SAN management by networking core and edge switches under a common management platform based on Brocade Fabric OS. An embedded real-time operating system, Fabric OS includes standard management interfaces, a full range of management tools, and a Brocade Fabric Access API that supports third-party SAN management applications. This open systems approach enables heterogeneous device connectivity, automatic data routing, and a seamless upgrade path among all SilkWorm products.

To simplify SAN administration and reduce management costs, the SilkWorm 3900 supports the following functions:

- Simple Network Management Protocol (SNMP)-based interfaces to

access switch information

- Switch management through a command line interface, WEB TOOLS, or Fabric Manager
- End-to-end fabric visibility through Advanced Performance Monitoring
- Real-time health monitoring through Fabric Watch
- Third-party SAN management application development through the Fabric Access API

#### SEAMLESS UPGRADES AND INVESTMENT PROTECTION

To protect existing investments, the SilkWorm 3900 provides backward and forward compatibility with the SilkWorm family of switches. In addition, translative mode capabilities enable legacy private loop devices to join the Fibre Channel SAN fabric.

The SilkWorm 3900 integrates with heterogeneous environments that include operating systems such as Windows NT, UNIX, and Linux—giving organizations the flexibility to select storage solutions that best match their particular needs. As a result, these organizations can more easily implement cost-efficient and highly manageable enterprise SAN fabrics.

#### HIGHER FABRIC SECURITY FOR CRITICAL INFORMATION

The SilkWorm 3900 is designed to provide the highest level of SAN fabric security to help organizations safeguard their critical information. For example, Brocade Zoning logically groups a SAN fabric into secure zones to help ensure that SAN-attached devices can access only their authorized storage resources. Advanced Zoning provides even more control over the fabric through robust hardware-enforced zoning by WWN. These capabilities enable organizations to simplify administration while significantly increasing their control over data access.

#### MAXIMIZING SAN INVESTMENTS

Brocade and its partners offer complete SAN solutions to meet a wide range of technology and business requirements. These solutions include education and training, support, service, and professional services to help optimize SAN investments. For more information, contact an authorized Brocade sales partner or visit [www.brocade.com](http://www.brocade.com).

## FIBRE CHANNEL STANDARDS AND REVISIONS

FC-AL-2 Rev 7.0	FC-FLA Rev 2.7	FC-GS-3 Rev 7.01	FC-FG Rev 3.5	FC-FS Rev 1.7
FC-PH Rev 4.3	FC-PH-2 Rev 7.4	FC-PH-3 Rev 9.4	FC-PLDA Rev 2.1	FC-SW-2 Rev 5.4
FC-VI Rev 1.6	IPFC RFC 2625			

## Systems Architecture

<b>Fibre Channel ports</b>	32 universal ports (E, F, and FL)
<b>Interoperability</b>	SilkWorm 2000, 3000, and 12000 switches
<b>Performance</b>	Auto-sensing of 1 Gbit/sec and 2 Gbit/sec port speeds
<b>ISL Trunking</b>	Up to four 2.125 Gbit/sec ports per trunk; up to 8.5 Gbit/sec per ISL trunk
<b>Aggregate bandwidth</b>	128 Gbit/sec end-to-end
<b>Switch core</b>	Non-blocking
<b>Fabric latency</b>	<2.1 $\mu$ sec. with no contention, cut-through routing
<b>Maximum frame size</b>	2112-byte payload
<b>Classes of service</b>	Class 2, Class 3, Class F (inter-switch frames)
<b>Port types</b>	FL_Port, F_Port, and E_Port; self-discovery based on switch type (U_Port); optional port type control
<b>Data traffic types</b>	Fabric switches support unicast, multicast (256 groups), and broadcast
<b>Media types</b>	Hot-pluggable, industry-standard Small Form-Factor Pluggable (SFP), LC connector; Short-Wavelength Laser (SWL); Long-Wavelength Laser (LWL); Extended Long-Wavelength Laser (ELWL); distance depends on fiber optic cable and port speed
<b>Laser</b>	Short-wave, long-wave, and extended long-wave
<b>Fabric services</b>	Simple Name Server, Registered State Change Notification (RSCN), Alias Server (multicast), and Brocade Zoning, Advanced Zoning, Extended Fabrics, Fabric Watch, ISL Trunking, and Remote Switch (some services are optional)
<b>Options</b>	Redundant power supply, and rack-mount kit
<b>Management</b>	
<b>Supported software</b>	Telnet, SNMP, WEB TOOLS, and Fabric Manager (optional)

<b>Management access</b>	10/100 Ethernet (RJ-45), serial port
<b>Diagnostics</b>	POST and embedded online/offline diagnostics

## Mechanical Specifications

<b>Enclosure</b>	Back-to-front airflow, power from rear 1.5U, 19-in.-EIA compliant
<b>Size</b>	Depth: 58.56 cm (23.06 in.) Height: 6.55 cm (2.58 in.) Width: 42.86 cm (16.87 in.)
<b>Weight</b>	Single power supply weight: 14.33 kg (31.60 lbs) Double power supply weight: 16.24 kg (35.80 lbs)
<b>Mounting option</b>	Rack-mountable in standard rack; Telco-style mid-mounting

## Environment

<b>Temperature</b>	Operating: 10° C to 40° C (50° F to 104° F) Nonoperating: -25° C to 70° C (-13° F to 158° F)
<b>Humidity</b>	Operating: 20% to 85% non-condensing at 40° C (104° F) Nonoperating: 10% to 85% non-condensing, at 70° C (158° F)
<b>Altitude</b>	Operating: up to 3,000 m (9,800 ft) Nonoperating: up to 12 km (40,000 ft)
<b>Shock</b>	Operating: 80 G, 2.4ms, half-sine Nonoperating: 20 G, 11 milliseconds, half-sine wave
<b>Vibration</b>	Operating: 0.5 G, 5-500 Hz Nonoperating: 2.0 G, 5-500 Hz
<b>Power</b>	
<b>AC Input</b>	Nominal: 100 to 240 VAC auto-ranging; 5.0 A
<b>Frequency</b>	47 to 63 Hz



**Corporate Headquarters**  
San Jose, CA USA  
T: (408) 487-8000  
info@brocade.com

**Asia Pacific Headquarters**  
Tokyo, Japan  
T: +81-3-5402-5300  
apac-info@brocade.com

**European Headquarters**  
Geneva, Switzerland  
T: +41 22 799 56 40  
europe-info@brocade.com

**Latin America Headquarters**  
Miami, FL USA  
(T): 305-716-4165  
latinam-sales@brocade.com

© 2003 Brocade Communications Systems, Inc. All Rights Reserved. 03/03 GA-DS-454-02

Brocade, the Brocade B weave logo, Secure Fabric OS, and SilkWorm are registered trademarks of Brocade Communications Systems, Inc., in the United States and/or in other countries. All other brands, products, or service names are or may be trademarks or service marks of, and are used to identify, products or services of their respective owners.

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered or to be offered by Brocade. Brocade reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This informational document describes features that may not be currently available. Contact a Brocade sales office for information on feature and product availability. Export of technical data contained in this document may require an export license from the United States government.